

PRODUCT DATA SHEET

ANDEROL C-NRT FGC 68

H1 Food Grade Inert Synthetic Compressor Lubricant

ADVANTAGES/BENEFITS

ANDEROL® synthetic lubricants are the only long-life synthetic lubricants with over 70 years of successful performance.

- Chemically inert to chemical gasses of acidic nature
- No metal additives to interfere with catalytic processes
- Increases maintenance intervals
- Greatly reduces fire and explosion hazard
- Lower oil consumption
- Eliminates lacquering and deposits completely
- Reduces energy consumption

COMPATIBILITY

ANDEROL® synthetic hydrocarbon based lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to an ANDEROL® synthetic hydrocarbon based lubricant.

APPLICATION

Cylinder and crankcase lubrication for screw, reciprocating and vane compressors for the following gases:

- Air
- Butadiene
- Carbon Monoxide
- Furnace (crack) gas
- Carbon Dioxide (dry)
- Ethylene
- Helium
- Hydrogen
- Fluoride gasses
- Hydrogen Sulfide (dry)
- Natural gas
- Methane
- Nitrogen
- Propane
- Synthesis Gas
- Sulfur Hexafluoride
- Bio gas

Nominal Operating Range -40°C to 170 °C.

ANDEROL C-NRT FGC 68 is a unique H1 registered synthetic lubricant meeting all requirements of air compressors running in food processing plants.

It is specifically designed to provide inertness and long-term lubrication in industrial applications, where contact with (reactive) chemistries cannot be avoided.

Where any other chemistry fails, this product will withstand attacks of all aggressive gasses and resist the rapid breakdown which is unavoidable with any other mineral/ester/PAO based product.

The complementary thermal and oxidative stability of the base fluid in combination with oxidation inhibitors, extends lubricant life at elevated temperature conditions.

Thanks to its excellent detergency effect deposit/lacquer formation is avoided.

ANDEROL C-NRT FGC 68 is certified Kosher by the Orthodox Union and Halal by the Islamic Food Council of Europe.

ANDEROL C-NRT FGC 68 meets or exceeds the following specifications: DIN 51506

PROPERTIES	TEST METHOD	ANDEROL C-NRT FGC 68
ISO VG	ASTM D-2422	68
Appearance @ 20°C	Visual	Clear Yellow Liquid
Viscosity @ 40°C, cSt	ASTM D-445	71.5
Viscosity @ 100°C, cSt	ASTM D-445	10.8
Viscosity Index	ASTM D-2270	140
Density @ 15°C, kg/l	ASTM D-1298	0.848
Total Acid Number, mg KOH/g	ASTM D-664	0.15
Flash Point, °C	ASTM D-92	240
Pour Point, °C	ASTM D-97	-48
Demulsibility @ 54°C, min	ASTM D-1401	10

FOR MORE INFORMATION PLEASE REFER TO THE RELEVANT MATERIAL SAFETY DATA SHEET

REGISTRATIONS



ANDEROL®
Specialty Lubricants

Groot Egtenrayseweg 23, 5928 PA Venlo, The Netherlands • Tel: +31 (0)77 3960340 • www.anderol-europe.com

This information is furnished without warranty, representation, inducement, or license of any kind except that it is accurate to the best of OUR knowledge or obtained from sources believed by ANDEROL® to be accurate. ANDEROL® does not assume any legal responsibility for use of reliance upon it. Only Chemists or chemically qualified lab technicians should carry out tests. Before using any chemicals, read its label and Material Safety Data Sheet.