

Anderol[®] 495

Anderol[®] Industrial lubricants compressors and vacuum pumps

Description

Synthetic Compressor Lubricant

Anderol[®] 495 is an ISO 32 synthetic Di-ester based compressor lubricant specifically designed to provide long-term lubrication in air and process gas compressors and vacuum pumps.

Anderol[®] 495 meets or exceeds the following specifications:

DIN 51506 VDL
ISO 6743-3 L-DAJ

Features and Benefits

- No metal additives to interfere with catalytic processes.
- Fewer oil changes.
- Increases maintenance intervals.
- Greatly reduces fire and explosion hazard.
- Separates water condensate rapidly.
- Lower oil consumption.
- Eliminates lacquering and deposits.
- Reduces energy consumption.

Compatibility

The following seals, paints and plastics are recommended for use in contact with **Anderol[®]** synthetic lubricants. Materials not recommended are also shown. For more information on other materials see our 'Compatibility Guide'.

RECOMMENDED:

Viton, High Nitrile Buna N, Teflon, Epoxy Paint, Oil-Resistant Alkyd, Nylon, Delrin, Celcon, PBT

NOT RECOMMENDED:

Neoprene, SBR Rubber, Low Nitrile Buna N, Acrylic Paint, Lacquer, Polystyrene, PVC, ABS



Anderol® 495

Anderol® Industrial lubricants compressors and vacuum pumps

Application

Anderol® 495 can be used for the lubrication of

- Oil flooded rotary screw compressors
- Oil flooded rotary vane compressors
- Axial compressors
- Centrifugal compressors & vacuum pumps

In the presence of the following gases:

Air	Ethylene	Methane
Butadiene	Helium	Nitrogen
Carbon Monoxide	Hydrogen	Propane
Furnace (crack) gas	Hydrogen Sulfide (dry)	Synthesis gas
Carbon Dioxide (dry)	Natural gas	Sulfur Hexafluoride

Nominal Operating Range -40°C to 230 °C

Approvals

- CompAir
- Renault
- Leybold
- Tamrock



Anderol[®] 495Anderol[®] Industrial lubricants compressors and vacuum pumps**Technical data***

PROPERTY	METHOD	ANDEROL 495
ISO VG	ASTM D-2422	32
Appearance @ 20°C	visual	Clear Yellow Liquid
Viscosity @ 40°C, cSt	ASTM D-445	28.0
Viscosity @ 100°C, cSt	ASTM D-445	5.4
Density @ 15°C, kg/l	ASTM D-1298	0.918
Total Acid Number, mg KOH/g	ASTM D-664	0.05
Flash Point, °C	ASTM D-92	260
Pour Point, °C	ASTM D-97	-56
Demulsibility @ 54°C, min	ASTM D-1401	24
Evaporation, 22 hrs @ 160°C, %	ASTM D-972	<1.0
Copper corrosion, 100 ° C	ASTM D-130	1B

**The analytical data are guide values.*

Anderol® 495

Anderol® Industrial lubricants compressors and vacuum pumps

Consult safety data sheet (SDS) for additional handling information on **Anderol® 495**
For registrations, certificates and approvals please refer to anderol.com

® = registered trade mark

This information and our technical advice – whether verbal, in writing or by way of trials – is subject to change without notice and given in good faith but without warranty or guarantee, express or implied, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

©2023 LANXESS and the LANXESS Logo are trademarks of LANXESS Deutschland GmbH or its affiliates. All trademarks are registered in many countries in the world.

North America
+1.833.LANXESS
customer.care@lanxess.com

Europe, Middle East & Africa
+31.77.396.0340
customerservice@anderol.com

South & Central America
+55.19.3522.5083
atendimento.cliente@lanxess.com

Asia Pacific
+86.21.6109.6666
Orders.apac@lanxess.com

